

Titanos® Ordinary Leafing Series Aluminum Paste

Description: Titanos® Ordinary Leafing Series Aluminum Paste, can float on surface of paint film, can effectively reflect light and heat, has good covering power and whiteness.

Application: Widely used in anticorrosion paint, reflective paint, paper paint, printing ink and etc.

Recommended Ratio in the Formulation: We suggest add 4~10% in the normal formulation and 15~20% in special formulation.

Packing Specification: 25KG/Metal Pail, 500KG/Pallet, 9Ton/20 Feet Container.

Grade	Particle Size D50 (μm)	Non Volatile (%)	Leafing Value (%)	Minimum Water Surface Covering Power (cm ² /g)	Solvent	Wet Sieve Pass Rate (%) 325 mesh
TS4115	Approx. 15	Approx. 62	Approx. 85	28000	MS/HA	99.0
TS4120	Approx. 20	Approx. 62	Approx. 90	60000	MS/HA	99.0

Titanos® Senior Leafing Series Aluminum Paste

Description: Titanos® senior Leafing Series Aluminum Paste, can float on surface of paint film, can effectively reflect light and heat, has good covering power, whiteness and brightness, can generating mirror effect in the low acid value resin system.

Application: Widely used in anticorrosion paint, reflective paint, paper paint, printing ink and etc.

Recommended Ratio in the Formulation: We suggest add $4\sim10\%$ in the normal formulation and $15\sim20\%$ in special formulation.

Packing Specification: 25KG/Metal Pail, 500KG/Pallet, 9Ton/20 Feet Container.

Grade	Particle Size D50 (μm)	Non Volatile (%)	Leafing Value (%)	Minimum Water Surface Covering Power (cm²/g)	Solvent	Wet Sieve Pass Rate (%) 325 mesh
TS4508	Approx. 8	Approx. 62	Approx. 95	45000	MS/HA	99.0
TS4514	Approx. 14	Approx. 62	Approx. 95	50000	MS/HA	99.0
TS4515	Approx. 15	Approx. 62	Approx. 95	60000	MS/HA	98.0
TS4516	Approx. 16	Approx. 62	Approx. 95	55000	MS/HA	98.0

Welcome to contact us by the following message, in order to get more product informations, samples and technical support services: