

First choice for new formulations

Issue No. 02/Feb-17

Reviewed in: Jun-18

Sudaperm™ Pink 2997C

Pigment for Coatings

Product Description

Quinacridone bluish red pigment with excellent rheology, suitable for high pigment loading color concentartes, outstanding light & weather fastness properties, suitable for all types of coatings.

Product Information

Chemical Type	Quinacridone	CAS NO.	980-26-7
C. I. Name	Pigment Red 122	EINECS / ELINCS NO.	213-561-3
C. I. Constitution No.	73915	Physical Appearance	Pink powder

Application Profile

Decorative Paints	•	Universal Stainers	•
Industrial Paints	•	Water Base Paints	•
Automotive OEM	•	Powder Coatings	•
Automotive Refinish	•		

• Recommend | O Potential Use | -- Not recommended

Technical Performance

Resistance to Alkali

Heat Stability	Overspray Fastness		Full Shade	Tint
180°C	5	Weather Resistance	5	4
		Light Fastness	8	7

Physical Properties			
Oil Absorption	55 ± 10%	Bleeding in Xylene	5
Specific Gravity	1.55 ± 0.1	Bleeding in Methyl Ethyl Ketone	4
Bulk Density (g/ml)	0.46 ± 0.1	Bleeding in Ethyl Acetate	5
pH Value	6 - 8	Bleeding in Cellosolve	2
Volatile Matter	1.3% max	Bleeding in Mineral Turpentine	5
Resistance to Acid	4	Specific Surface Area (m²/g)	58.8

Average size of Primary Particle (nm)

✓ Light fastness: Light fastness rating is assessed on 1 to 8 Blue Wool scale where 1 = 'Poor' and 8 = 'Excellent'.

3

- √ Weather fastness: Weather fastness rating is assessed on 1 to 5 Grey scale where 1 = 'Poor' and 5 = 'Excellent'.
- ✓ Heat stability: Heat stability values given indicate the maximum temperature at which the pigments can be stoved for 10 min. in the full shade and in reductions without undergoing any significant change in shade.
- ✓ Oil absorption: The oil absorption was determined on the basis of EN ISO 787-5 and given in linseed oil per 100 gm. pigment.
- ✓ Solvent bleeding: The bleeding in solvents was tested using the powder grades and the visual rating given on 1 to 5 Grey scale where 1 = 'Heavy bleeding' and 5 = 'No bleeding

The above information is for guidance only and to the best of our knowledge it is accurate and reliable. However, as use conditions are not within our control, no guarantees are given or are to be inferred. Test methods used to generate this data can be provided on request.