

Technical Data Sheet

Version: 2.2

TITANOS TA100 Anatase Titanium Dioxide Pigment

Description	TA100 is a multi-purpose anatase titanium dioxide with sulfate process. It has good whiteness and easy dispersion.
Applications	It is recommended for evaluation in: <ul style="list-style-type: none"> • Both interior and exterior decorative architectural coating. • Automotive painting. • Road mark painting. • Wood painting, • Refinish painting • Marine painting. • Printing ink.
Typical Properties	TiO ₂ Content: ≥98% Organic Treatment : No Specific Gravity (g/cm ³): 3.9 Oil Absorption (g/100g): ≤ 25 pH Value: 6.5 – 8.5 Tinting (compared with standard sample): ≥ 100 Residue on sieve of 45 μm (m/m): ≤ 0.05% Water Soluble: ≤0.5% Color(compared with standard sample): Not lower than
Classifications	ISO 591: A1 ASTM D-476-00: Type I CAS No.: 13463-67-7 Color Index: 77891 Pigment white 6
Storage	Keep the product un-stacked in dry and closed rooms at normal temperature and good air humidity. To achieve best possible results, we recommend storage under the condition stated above and use within 12 months from delivery.
* Typical Properties not to be construed as specifications	

WWW.TITANOS.COM

Disclaimer:

The information given in this publication is obtained from sources believed to be reliable and every effort has been made to ensure that the data is correct and not misleading. However, Titanos group accepts no responsibility for any errors, omissions or incorrect information or for any loss or consequential losses.