

Type

Packing

Transportation Safety

## FOSHAN SANSHUI BAIXIN CHEMICAL CO., LTD

Rutile titanium dioxide R5188S

ADDRESS: 9 /SECTION B, SOUTHWEST INDUSTRIAL PARK, SANSHUI, FOSHAN

WEBSITE: https://www.bb-hy.com/

EMAIL: vat@bb-hy.com

## **TDS**

Classification	Rutile titanium dioxide R5188S conforms to:		
	ISO 591-1-2000 Typ	pe R2	
	ASTM D476-84 Туր	pe II	
Feature	R5188 is a multipurpose Rutile titanium dioxide pigment,		
	manufactured by sulphate process, which is designed to give		
	outstanding combination of high gloss, high dispersibility,		
	durability and high weather re	esistance.	
Application:	Water and solvent-based coating, high gloss exterior and interior Wall emulsion paint, plastic and masterbatch		
Typical properties	TiO2 content,%	≥93.5	
	Matter Volatile at 105°C,% .	≤0.5	
	PH Value of aqueous suspe	ension6.0-8.5	
	Oil absorption,g/100g	≤22	
	Residue on sieve(45µm),%≤0.05		
	Tint-Reducing power(Reynolds number)≥115		
	Brightness,≥94.5		
	Rutile content,%>98		
	Specific Resistance, $\Omega$ .m $\geqslant$ 60		
	Oil dispersion (Hegman)≥6		
	Surface treatmentCoated with ZrO <sub>2</sub> & Al <sub>2</sub> O <sub>3</sub> and organic		

25KG paper bag; 500KG jumbo bag; 1000KG jumbo bag.

Keep it free from sunshine, rain and high-temperature.

goods when move it.

Keep the package in good condition and keep the stability of the