TAND5上海颜钛实业有限公司 SHANGHAI TITANOS INDUSTRY CO., LTD.

ADD: ROOM 2101. NO. 915 ZHENBEI ROAD, SHANGHAI 200333, P.R. OF CHINA. TEL: +86-21-32513559/32513560 FAX: +86-21-32513556 E-mail: sales@titanos.com.cn

Technical Data Sheet

Version: 3.0

TITANOS R903 Rutile Titanium Dioxide Pigment

Applications	It is recommended for evaluation in: Polyethylene Masterbatch Polystyrene Polypropylene Plastics ABS Flexible PVC TiO2 Content:	
Typical Properties	TiO2 Content:	
	Organic Treatment: Inorganic Treatment: Specific Gravity (g/cm3): Oil Absorption (g/100g): pH Value: Residue on sieve of 45 µm (m/m):	$\geq 96\%$ Yes 4.1 ≤ 18 6.5 - 8.5 $\leq 0.1\%$
Classifications	ISO 591: ASTM D-476-00: CAS number: Color Index:	R2 Type II 13463-67-7 77891 Pigment white 6
4	Keep the product un-stacked in dry and closed rooms at normal temperature and air humidity. To achieve best possible results, we recommend storage under the condition stated above and use within 12 months from delivery.	

WWW.TITANOS.COM

The information given in this publication is obtained from sources believed to be reliable and every effort has been made to ensure that the data is correct and not misleading. However, Titanos accepts no responsibility for any errors, omissions or incorrect information or for any loss or consequential losses.

Disclaimer: