

## Technical Data Sheet

Version: 2.0

### TITANOS R900 Rutile Titanium Dioxide Pigment

Description	R900 is an excellent general-purpose grade rutile titanium dioxide pigment designed with good gloss, excellent opacity, easy dispersion and nice whiteness.
Applications	It is recommended for evaluation in: <ul style="list-style-type: none"><li>• Both interior and exterior painting.</li><li>• Solvent and water painting.</li><li>• Masterbatch, plastic, PVC.</li><li>• Inks, leather, rubber etc.</li></ul>
Typical Properties	<div>TiO<sub>2</sub> Content: ≥ 92 %</div> <div>Organic Treatment: Yes</div> <div>Inorganic Treatment: Yes</div> <div>Specific Gravity (g/cm<sup>3</sup>): 4.1</div> <div>Oil Absorption (g/100g): ≤ 20</div> <div>pH Value: 6.0 – 8.5</div> <div>Residue on sieve of 45 μm (m/m): ≤ 0.05%</div>
Classifications	<div>ISO 591: R2</div> <div>ASTM D-476-00: Type II</div> <div>CAS number: 13463-67-7</div> <div>Color Index: 77891</div> <div>Pigment white 6</div>
Storage	Keep the product un-stacked in dry and closed rooms at normal temperature and air humidity. To achieve best possible results, we recommend storage under the condition stated above and use within 12 months from delivery.
* Typical Properties not to be construed as specifications	

WWW.TITANOS.COM

**Disclaimer:**

The information given in this publication is obtained from sources believed to be reliable and every effort has been made to ensure that the data is correct and not misleading. However, Titanos accepts no responsibility for any errors, omissions or incorrect information or for any loss or consequential losses.